



PERSPECTIVES

Fire-Hardened Residential Construction: Good Practices and Emerging Technologies for Wild fire Resilience

Our perspectives feature the viewpoints of our subject matter experts on current topics and emerging trends.

INTRODUCTION

As wildfires increase in frequency and severity, the construction industry is turning to advanced fire-resistant building techniques and materials to create “fire-hardened” homes that can withstand extreme heat, direct flames, and wind-driven embers. While California’s Wildland-Urban Interface (WUI) codes (CBC Chapter 7A) set minimum fire-resistance standards, advancements in materials, construction techniques, and technologies now allow builders and homeowners to exceed these requirements for superior protection.

This report explores:

- Fire-resistant and advanced building materials.
- Innovative construction techniques.
- Emerging technologies.
- Case study: Malibu’s “miracle mansion.”

KEY CONSIDERATIONS FOR FIRE-HARDENED HOMES

To reduce wildfire risk, Class A fire-resistant materials should be used for roofing, siding, and decking. Limiting combustible materials in walls, insulation, and decks further prevents ignition. Eliminating ember entry points, such as vents, eaves, and windows, is crucial. Sealed vents, fire-rated windows, and noncombustible soffits provide critical protection.

Fire suppression and early detection technologies, such as automated sprinklers, ember-resistant vents, and AI-powered wildfire detection, add an extra layer of defense. Proper site planning—maintaining a five-foot noncombustible perimeter and using fire-resistant landscaping—reduces the risk of direct flame contact. By combining fire-resistant construction, ember-proofing, and suppression technology, homes can be significantly more resilient to wildfire threats.

Residences or structures located in a Fire Hazard Severity Zone, as per [CalFire Fire Hazard Severity Zone Maps](#) and the California Fire Code, must have 100 feet of defensible open space around all residences and 10 feet of defensible space along each side of

driveways and roads. Additional driveway and fire hydrant requirements may apply to new or replacement structures, depending on the driveway length and dwelling size. Some County Fire Codes may impose further requirements.

Replacement structures must be reconstructed in compliance with the requirements for Moderate or Severe Fire Severity Zones (HFSZ or SFSZ) and adhere to the wildfire protection provisions outlined in the California Residential Code (CRC) R337 and the California Building Code (CBC), including:

- Section 704A: Ignition-Resistant Construction.
- Section 705A: Roofing.
- Section 706A: Vents.
- Section 707A: Exterior Covering.
- Section 708A: Exterior Windows and Doors.
- Section 709A: Decking.
- Section 710A: Accessory Structures.

The following components require special attention or alternative materials to meet fire-resistant standards.

FIRE-RESISTANT AND ADVANCED BUILDING MATERIALS

Roofing (Class A Required) – UL790 or ASTM E108

The roof is one of the most vulnerable areas, and Class A roofing materials provide the highest level of fire resistance.

- Clay or concrete tile—hips and ridge caps must be mudded to prevent the intrusion of embers.
- Metal roofing.
- Slate roofing.
- Fire-retardant treated wood shingle/shakes—approved/listed by CA State Fire Marshal.
- Fire-resistant composite roofing.
- Gutters—all gutters must be equipped with debris guards to prevent the accumulation of flammable materials.

Best practices for fire-hardened roofing include installing fire-hardened underlayment to provide additional protection beneath the roof covering. Additionally, using sealed edges and metal flashing helps prevent ember intrusion, reducing the risk of ignition during a wildfire. Use of a Class A roofing underlayment is also required if the roof decking is not fire-retardant treated wood.

Exterior Walls and Siding

Noncombustible or ignition-resistant siding materials are essential for reducing fire spread and radiant heat ignition per ASTM E2707.

- Fiber-cement siding (e.g., HardiePlank®)—used for siding or trim.
- Stucco—three-coat cement plaster.
- Brick or stone veneer.
- Metal siding.
- Fire-retardant treated (FRT) wood—used for siding or trim.
- Heavy timber—solid lumber or glue-laminated lumber with a minimum dimension of over four inches thick or deep.
- Log wall construction.
- One-hour fire rated exterior construction—must be tested in accordance with ASTM E119 or UL 263 by an independent testing laboratory.
- Architectural features—all bump-outs, overhangs, and projections must utilize fire-resistant materials or construction techniques to reduce fire vulnerability.

Fire-rated sheathing (5/8-inch Type X gypsum) should be used behind the siding for additional resistance, and it is important to ensure the presence of tight joints and noncombustible backing to prevent embers from entering wall cavities.

Glazing, Doors, and Vents

Openings in a home's envelope—windows, doors, and attic vents—are critical weak points in fire defense.

- Dual-pane windows or skylights—must have a tempered glass outer pane.
- Fire-rated doors and glass—minimum 20-minute fire rating.

- Glass block windows.
- Metal-skinned doors and frames—includes garage doors.
- Wildland flame & ember-resistant vents—must be approved by the CA State Fire Marshal or use noncombustible venting materials that comply with ASTM E2886.
- Soffit and eave ventilation openings—should be protected using approved metal mesh or ember-resistant vents to block fire entry points.
- Soffits and walls—must be stucco-wrapped or constructed from fire-retardant siding.

Installing metal corrosion-resistant mesh screens (1/16-inch or 1/8-inch mesh) helps block embers and reduce the risk of ignition. Additionally, limiting the number and size of windows on fire-exposed sides of the home helps minimize vulnerability.

Insulation and Decking

Fire-resistant insulation and decking reduce fuel sources and slow fire spread.

- Mineral wool insulation.
- Dense pack cellulose.
- Concrete or metal decking—must be noncombustible.
- Class A fire-rated hardwoods—must comply with SFM Standard 12-7A-4A.
- Fire-retardant treated wood decking.
- Attached surface material—the surface material of attached structures (e.g., entry canopies or decks) or any portion of such structures within 10 feet of a building must be ignition-resistant, fire-retardant, or noncombustible, or comply with the performance requirements of SFM Standard 12-7A-4A.
- Accessory structures—structures within three to 50 feet of the principal dwelling and 120 square feet or larger must be built with noncombustible or ignition-resistant materials.

For enhanced fire resistance, elevated decks and porches should be constructed using concrete or metal whenever possible to minimize ignition risk. Maintaining a non-combustible five-foot perimeter around the structure is also essential to reduce exposure to embers and direct flames.

Fireproof Materials and Coatings

Recent advancements in nanotechnology have led to the development of fireproof coatings that significantly improve the heat resistance of traditional building materials. These coatings can be applied to wood, metal, and composite materials to prevent ignition and slow flame spread.

Additionally, self-healing coatings help repair microcracks caused by extreme heat, preserving their protective properties over time. Some coatings also incorporate insulative ceramic particles (ICP) technology, which reduces heat absorption and creates a thermal barrier, further enhancing fire resistance. These innovations offer a promising solution for improving residential structures' durability and wildfire resilience.

Important Note: According to California building codes, the use of paint, coatings, stains, or similar treatments is not an approved method of fire protection.

INNOVATIVE CONSTRUCTION TECHNIQUES

Insulated Concrete Forms (ICFs)

One of the most effective strategies for constructing fire-resistant homes is replacing traditional wood framing with noncombustible, insulated mass walls. Insulated concrete forms (ICFs) are a cutting-edge wall system that utilizes interlocking foam blocks filled with steel-reinforced concrete to create a monolithic, highly insulated structure.

ICF walls have demonstrated exceptional fire resistance; however, to ensure maximum protection, all exterior cladding must be ignition-resistant or noncombustible.

Prefabricated and Modular Fireproof Construction

Prefabricated fire-resistant panels enhance wildfire

resilience by offering noncombustible, high-performance materials while streamlining construction. These panels, which include composite cores for walls and roofing, arrive pre-finished and fire-rated, reducing the need for extensive on-site labor. To ensure maximum protection, materials should comply with WUI fire-resistance standards, and fire-resistant adhesives and fasteners should be used to maintain durability and integrity under extreme heat exposure.

EMERGING TECHNOLOGIES

AI-Powered Wildfire Detection

Artificial intelligence is revolutionizing wildfire detection by enabling AI-driven camera networks to identify fires before they are visible to the human eye. These systems continuously monitor landscapes, detecting smoke and heat signatures in real-time, allowing for rapid response. Additionally, satellite-based AI fire prediction models analyze environmental conditions to identify ignition risks in advance, helping communities prepare for potential wildfire threats before they escalate.

Automated Wildfire Suppression Systems

Smart fire suppression technologies are enhancing home protection by automating fire defense measures. Smart sprinkler systems activate when heat sensors detect nearby wildfires, soaking the home and surrounding vegetation to prevent ignition. Ember-resistant vents block airborne embers from entering attics and crawlspaces, while AI-controlled fire shutters automatically seal windows and doors when high temperatures are detected. Together, these systems provide an advanced, proactive defense against wildfires, reducing the risk of structural ignition.

CASE STUDY: MALIBU'S "MIRACLE MANSION"

In January 2025, a massive wildfire tore through Malibu, California, destroying thousands of homes in its path.

Among the devastation, one property stood unscathed—dubbed “Malibu’s miracle mansion”—a testament to the effectiveness of fire-resistant architecture, advanced materials, and strategic wildfire mitigation techniques. While many neighboring structures succumbed to the fire, this mansion remained intact, demonstrating how modern fire-hardening strategies can significantly improve a home’s survivability in extreme wildfire events.

Key design features of the mansion included:

- Reinforced concrete walls.
- Metal roofing.
- Dual-pane tempered glass windows and fire-rated doors.
- Five-foot noncombustible perimeter.
- Ember-resistant vents.
- Smart exterior sprinkler system.
- AI-powered fire detection.
- Fireproof materials and coatings.

CONCLUSION

Malibu’s “miracle mansion” demonstrates how fire-resistant materials, innovative construction techniques, and emerging technologies can significantly enhance a home’s wildfire survivability. By integrating noncombustible materials, ember-proofing, and smart suppression systems, knowledgeable experts can design homes in fire-prone areas to withstand extreme fire events and improve long-term resilience. Additionally, consulting experts with multidisciplinary expertise in wildfire risk, construction consulting, and code compliance, can help greatly when building smarter, safer, and more resilient structures in high-risk environments.

ACKNOWLEDGMENTS

We would like to thank Travis Sommerfeld, Adam Norman, and Erik Fritzberg, RA, CBO, CPHC, CFM, for their insight and experience, which greatly assisted this research.

[Travis Sommerfeld](#) is a Senior Vice President in J.S. Held’s Building Consulting Practice, overseeing a team of professionals across multiple regions. With over a decade of experience in construction consulting,

he has managed complex projects across residential, commercial, industrial, and institutional sectors, specializing in damage quantification, cost estimating, and large-loss assessments. Travis has provided expert consulting on high-net-worth properties, high-rises, hospitals, and university campuses. He has shared his industry knowledge through speaking engagements on building materials, construction scheduling, and restoration technologies.

Travis can be reached at tsommerfeld@jsheld.com or +1 724 815 5501

[Adam Norman](#) is Vice President of Operations – Client Success within J.S. Held’s Building Consulting Practice. In this role, Adam is responsible for enhancing quality assurance, operational efficiency, and client experience across insurance-facing practices. He plays a key role in developing and implementing technology-driven, expert-based services that improve service delivery and streamline complex processes. His extensive experience includes leading large-scale, KPI-driven teams in the insurance and claims industry and earning meritorious promotions during his military service. Adam’s ability to build strong client relationships, drive operational improvements, and lead complex projects makes him an integral part of J.S. Held’s ongoing innovation and success.

Adam can be reached at anorman@jsheld.com or +1 857 767 2125

[Erik Fritzberg](#) is a Senior Architect with extensive licensure in J.S. Held’s Forensic Architecture and Engineering Practice and a professional mitigation, construction, and building code expert specializing in the application of code-required upgrades as they apply to existing buildings. Erik also assists with all aspects of building shell and assembly design and specification. Erik’s experience with numerous institutional, commercial, educational, industrial, and residential projects of various construction types and complexities, both new and existing, provides him with a broad range of expertise to assist owners and clients.

Erik can be reached at efritzberg@jsheld.com or +1 412 293 3756

REFERENCES & RESOURCES

- [California Department of Housing and Community Development | Wildland-Urban Interfaces](#)
- [Office of the State Fire Marshal | Building Materials Listing](#)
- [National Fire Protection Association \(NFPA\) | Preparing Homes for Wildfire](#)
- [University of California, Berkley Forests | Building in Wildfire-Prone Areas](#)
- [Fire Safe Marin | Adapting to Wildfire Means Being Prepared](#)
- [Rick Somers Construction, Inc. | Fire-Resistant Materials for Wildfire Resilience](#)
- [Rick Somers Construction, Inc. | Understanding Chapter 705A of The California Building Code: Fire-Resilient Homes](#)
- [Fire & Safety Journal Americas | Advancements in Fire Resistant Materials](#)
- [Roof Evolution | Discover the Most Fire-Resistant Roofing Materials](#)
- [Allied Disaster Defense | Ember Resistant Vents](#)
- [Wildfire Partners | Properly Screening Vents to Prevent Ember Incursion](#)
- [ROCKWOOL | WUI Building Codes: Designing Buildings to Prevent Loss](#)
- [LumberPlus | Ipe Fire Rating: Ensuring Class A Decking Safety](#)
- [LumberPlus | Fire-Resistant Decking: Exploring the Best Material](#)
- [Rick Somers Construction, Inc. | Revolutionary Innovations in Fire-Resistant Building Technologies](#)
- [NanoTech Materials Inc. | Cool Roof, Insulative, and Fireproof Coatings](#)
- [The Concrete Centre | Fire Resistance](#)
- [BuildBlock Building Systems LLC | Insulated Concrete Forms \(ICF\) Construction Systems](#)
- [Nexcem Inc. | Insulated Concrete Forms](#)
- [Element ICF | Hardening Your Home Against Wildfires: How ICFs Can Help](#)
- [ABC7 Los Angeles | Santa Clarita Family Using Fireproof ICF Technique to Rebuild Home After 2019 Tick Fire](#)
- [Dryad Networks | Ultra Early Wildfire Detection](#)
- [Pano AI | Advanced Wildfire & Bushfire Detection Technology](#)
- [Frontline Wildfire Defense | Wildfire Protection for Homes & Businesses](#)
- [NBC Los Angeles | Teen Innovator Develops AI-Powered Wildfire Sensor to Detect Flames Before They Spread](#)
- [New York Post | How Malibu's 'Miracle' Mansion Survived the LA Wildfires](#)

This publication is for educational and general information purposes only. It may contain errors and is provided as is. It is not intended as specific advice, legal, or otherwise. Opinions and views are not necessarily those of J.S. Held or its affiliates and it should not be presumed that J.S. Held subscribes to any particular method, interpretation, or analysis merely because it appears in this publication. We disclaim any representation and/or warranty regarding the accuracy, timeliness, quality, or applicability of any of the contents. You should not act, or fail to act, in reliance on this publication and we disclaim all liability in respect to such actions or failure to act. We assume no responsibility for information contained in this publication and disclaim all liability and damages in respect to such information. This publication is not a substitute for competent legal advice. The content herein may be updated or otherwise modified without notice.

J.S. Held, its affiliates and subsidiaries are not certified public accounting firm(s) and do not provide audit, attest, or any other public accounting services. J.S. Held is not a law firm and does not provide legal advice. Securities offered through PM Securities, LLC, d/b/a Phoenix IB or Ocean Tomo Investments, a part of J.S. Held, member FINRA/SIPC. All rights reserved.